MapReduce

Aiichiro Nakano

Collaboratory for Advanced Computing & Simulations Department of Computer Science Department of Physics & Astronomy Department of Quantitative & Computational Biology University of Southern California

Email: anakano@usc.edu




Amazon Elastic Computing Cloud (EC2) <u>Cloud computing support at CARC</u> <u>Hadoop@USC-HPC</u>



Above the Clouds: A Berkeley View of Cloud Computing





IoT: Internet of things

MapReduce

- Parallel programming model for data-intensive applications on large clusters
 - >User just implements Map() and Reduce()
- Parallel computing framework
 - >Libraries take care of everything else
 - Parallelization
 - Fault tolerance
 - Data distribution
 - Load balancing
- Developed at Google

Functional Abstraction

 Map and Reduce functions borrowed from functional programming languages

(Common LISP example)

- > (mapcar '1+ '(1 2 3 4)) \Rightarrow (2 3 4 5)
- > (reduce '+ '(1 2 3 4)) \Rightarrow 10
- Map()
 - > Process a key/value pair to generate intermediate key/value pairs
- Reduce()

```
cf. MPI_Allreduce()
```

> Merge all intermediate values associated with the same key

cf. Lambda function


Lisp: ((lambda (x y) (+ x y)) 1 2)
DPC++: q.submit([&](handler &h){ Command group })

Example: Counting Words

- Map()
 - > Input <filename, file text>
 - > Parses file and emits <word, count> pairs
 - *e.g.* <"hello", 1>
- Reduce()
 - > Sums values for the same key and emits <word, TotalCount>
 - *e.g.* <"hello", (3 5 2 7)> ⇒ <"hello", 17>

```
map(String key, String value):
// key: document name
// value: document contents
for each word w in value:
    EmitIntermediate(w, "1");
reduce(String key, Iterator values):
// key: a word
// values: a list of counts
int result = 0;
for each v in values:
    result += ParseInt(v);
Emit(AsString(result));
```

Parallel Execution



MapReduce Resources

- Hadoop implementation http://hadoop.apache.org
- MapReduce tutorial

https://hadoop.apache.org/docs/current/hadoop-mapreduceclient/hadoop-mapreduce-client-core/MapReduceTutorial.html

• Paper

J. Dean and S. Ghemawat, <u>MapReduce: simplified data processing on large</u> <u>clusters</u>, *Communications of the ACM* **51(1)**, 107 ('08)

• Free account (Amazon Web Services) http://aws.amazon.com/free

Cloud Supercomputing

TECHNOLOGY LAB / INFORMATION TECHNOLOGY

18 hours, \$33K, and 156,314 cores: Amazon cloud HPC hits a "petaflop"

1.21 petaflops? Great scott!

by Jon Brodkin - Nov 12 2013, 11:00am PST



USC chemistry professor Mark Thompson needed the cluster to design materials that might be well-suited to converting sunlight into solar energy.

"For any possible material, just figuring out how to synthesize it, purify it, and then analyze it typically takes a year of grad student time and hundreds of thousands of dollars in equipment, chemicals, and labor for that one molecule," Cycle Computing CEO Jason Stowe wrote in a blog post today.

Instead of doing that, Thompson uses simulation software made by Schrödinger. With that software running on Amazon, Thompson was able to simulate 205,000 molecules and do the equivalent of 2.3 million hours of science (counting the compute time for each core separately). The cluster ran only last week, so it's too early to find out what its impact on solar science will be. Still, from a computing standpoint, it's impressive.

National Strategic Computing Initiative

• July 29, 2015: President Obama issued an executive order

EXECUTIVE ORDER

CREATING A NATIONAL STRATEGIC COMPUTING INITIATIVE

BARACK OBAMA

By the authority vested in me as President by the Constitution and the laws of the United States of America, and to maximize benefits of high-performance computing (HPC) research, development, and deployment, it is hereby ordered as follows:



• NSCI will merge exaflop/s (10¹⁸ floating-point operations per second) high performance computing (HPC) & exabyte (10¹⁸ bytes) "big data" to advance the frontier of sciences, economic growth & national security